

VL5 is the chain block of the wonderful performance.

For plated parts, we use trivalent chromate treatment, which is environment friendly.









Laying conduits and pipelines

Uprooting

trees

VITAL brand is registered worldwide.






VITAL CHAIN BLOCK MFG.CO.,LTD.


ISO 9001 Certificate No.JQA-QM4488

VITAL CHAIN BLOCK VL5 Series



Specifications

Capacity	Model Number	Model Lift Weight Weight Lift Load		Head Room C	а	b	g	Test Load			
(t)		(m)	(kg)	(kg)	(kgf)	(N)	(mm)	(mm)	(mm)	(mm)	(t)
1⁄2	VL5-05	2.5	8.3	8.7	25	245	285	129	145	27	0.75
1	VL5-10	2.5	11.3	11.8	33	324	315	149	158	30	1.5
1 ¹ ⁄2	VL5-15	2.5	13.5	14.0	34	333	340	149	177	34	2.25
2	VL5-20	3.0	21.0	22.2	34	333	380	181	204	37	3.0
3	VL5-30	3.0	22.0	22.7	35	343	475	149	208	43	4.5
5	VL5-50	3.0	40.0	41.5	39	382	600	181	263	47	7.5
7 ¹ ⁄2	VL5-75	3.5	59.0	66.5	41	402	700	181	354	67	9.5
10	VL5-90	3.5	77.0	84.5	41	402	740	181	367	67	12.5



Hoists with the lift in other lengths are also available.

"VL5" Series With a hardened special alloy steel load chain.

Vital offers products that are designed for longtime use, providing the lowest possible per-use cost.

Please note that the specifications on this leaflet may be modified for improvements without notice

Since 1998 VITAL CHAIN BLOCK MFG. CO., LTD.